

TS SONIC[®] Bench scale series



24 X 30



40 X 50



60 X 70



40 X 50 + Back grill



FEATURES

- Strong mild steel construction
- Stainless steel cover plate
- High quality load cell
- Overload load cell protection
- Full press body (24 X 30 cm)
- Suitable for industrial environment
- 100% corner adjusted

OPTION

- Back grill
- 304 stainless steel

OPTIONAL INDICATOR



SPECIFICATION

Model	Specification									
Platter size	24 x 30 cm	30 x 40 cm	40 x 50 cm	50 x 60 cm	60 x 70 cm	60 x 80 cm	70 x 80 cm			
Capacity	6 kg, 15 kg	30 kg, 60 kg, 75 kg	75 kg, 150 kg	150 kg, 300 kg, 500 kg	300 kg, 500 kg, 600 kg	300 kg, 500 kg, 600 kg	300 kg, 500 kg, 600 kg	300 kg, 500 kg, 600 kg	300 kg, 500 kg, 600 kg	300 kg, 500 kg, 600 kg
Readability	0.5 g, 1 g	2 g, 5 g, 5g	5 g, 10 g	20 g, 50 g, 100 g	50 g, 100 g	50 g, 100 g	50 g, 0.1 kg	50 g, 0.1 kg	50 g, 0.1 kg	50 g, 0.1 kg
Dimension cm	41 (L) x 24 (W) x 38,5 (H)	49,5 (L) x 30 (W) x 46 (H)	60 (L) x 40 (W) x 66,5 (H)	76,5 (L) x 50 (W) x 81,5 (H)	70 (L) x 60 (W) x 103 (H)	70 (L) x 60 (W) x 103 (H)	80 (L) x 60 (W) x 103 (H)	80 (L) x 60 (W) x 103 (H)	80 (L) x 70 (W) x 103 (H)	80 (L) x 70 (W) x 103 (H)
Product weight	6,52 kg	5,42 kg	9,33 kg	17,36 kg	33 kg	33 kg	36 kg	36 kg	39 kg	39 kg
Load cell	L6D	L6E	L6E3	UDA	UDA	UDA	UDA	UDA	UDA	UDA
Indicator :	Sonic T10	Sonic NI-7	Sonic A1P	Sonic T18	Sonic A7	Sonic A12E	Sonic A15E	Sonic SP-320S	Sonic T6	Sonic A1-5
Display	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED	Red LED
Rechargeable battery	6V/4AH	6V/4AH	AC cable	6V/4AH	6V/2,8AH	6V/4AH	6V/4AH	6V/4AH	4V/4,5AH	6V/4AH
RS-232	-	✓	✓	✓	✓	✓	✓	✓	-	✓
Material	Abs	Abs	Abs	Abs	Abs	Abs	Abs	Stainless steel	Abs	Abs
Resolution	1/30.000	1/30.000	1/30.000	1/30.000	1/30.000	1/30.000	1/30.000	1/40.000	1/30.000	1/30.000
Printer	-	-	Dot matrik	-	-	-	-	-	-	-
Wall bracket	-	-	-	✓	-	-	-	✓	-	-