



AJ(H)-220(C)E~620(C)E



AJ-820(C)E/1200(C)E



AJ(H)-2200(C)E~4200(C)E  
AJ-6200(C)E~12K(C)E

## Specifications

- \*AJ-XXXCE stands for EC approval models.
- \*Dry cell battery type is available for each model.

Model	AJ-220E AJ-220CE	AJ-320E AJ-320CE	AJ-420E AJ-420CE	AJ-620E AJ-620CE	AJ-820E AJ-820CE	AJ-1200E AJ-1200CE	AJ-2200E AJ-2200CE	AJ-3200E AJ-3200CE	AJ-4200E AJ-4200CE	AJ-6200E AJ-6200CE	AJ-8200E AJ-8200CE	AJ-12KE AJ-12KCE
Capacity	220g	320g	420g	620g	820g	1220g	2200g	3200g	4200g	6200g	8200g	12000g
Readability	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g	0.01g	0.01g	0.01g	0.1g	0.1g
Repeatability(e)	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g	0.01g	0.01g	0.01g	0.1g	0.1g
Non-Linearity(typ.)	±0.001g	±0.001g	±0.001g	±0.002g	±0.01g	±0.01g	±0.01g	±0.01g	±0.01g	±0.02g	±0.1g	±0.1g
Pan size	φ118mm				170×142mm			180×160mm				
Dimensions	235×182×168mm(including windshield)				235×182×75mm			265×192×87mm				
Weighing units	g, ct, oz, lb, ozt, dwt, GN, t(Hong Kong), t(Taiwan), t(Singapore, Malaysia), momme, tola											
Power source	AC120/230V DC9V											
Output	RS-232C(standard)											
Measuring system	Tuning-fork frequency sensing (MMTS)											
Tare	Full weighing range											
Calibration	With external calibration weight											
Display	LCD(height: 16.5mm)											
Modes	weighing, counting, %											
Weight	Approx. 1.3kg						Approx. 2.8kg					

Model	AJH-220E AJH-220CE	AJH-320E AJH-320CE	AJH-420E AJH-420CE	AJH-620E AJH-620CE	AJH-2200E AJH-2200CE	AJH-3200E AJH-3200CE	AJH-4200E AJH-4200CE
Capacity	220g	320g	420g	620g	2200g	3200g	4200g
Readability	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g
Repeatability(s)	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g
Non-Linearity(typ.)	±0.001g	±0.001g	±0.001g	±0.002g	±0.01g	±0.01g	±0.01g
Pan size	φ118mm				180×160mm		
Dimensions	235×182×168mm(including windshield)				265×192×87mm		
Weighing units	g, ct, oz, lb, ozt, dwt, GN, t(Hong Kong), t(Taiwan), t(Singapore, Malaysia), momme, tola						
Power source	AC120/230V DC9V						
Output	RS-232C(standard)						
Measuring system	Tuning-fork frequency sensing (MMTS)						
Tare	Full weighing range						
Calibration	With built-in weight						
Display	LCD(height: 16.5mm)						
Modes	weighing, counting, %						
Weight	Approx. 1.6kg				Approx. 3.7kg		

## Options & Peripherals

- AJBT(S)/AJBT(M)  
Rechargeable battery  
(S) for AJ(H)-220(C)E~1200(C)E  
(M) for AJ(H)-2200(C)E~12K(C)E  
(12-hr charge, 32-hr operation)
- AJUH(S)/AJUH(M)  
Under weighing hook  
(S) for AJ(H)-220(C)E~1200(C)E  
(M) for AJ(H)-2200(C)E~12K(C)E
- SDI/SDR Satellite display
- RTS Database software for Windows

## Dimensions

